


Series: LOD-HTH, BOD-HTH, LOD-ALTH, BOD-ALTH, LOD-GTH, BOD-GTH
**Welded steel heavy duty
double swivel and fixed castors**

 500 - 800 kg



Swivel castors **Fixed castors**


Brackets: LOD/BOD Series - Heavy welded steel construction, swivel bracket with double ball bearing in the swivel head, **additionally reinforced by the integration of four specially shaped and hardened bearing seats**, labyrinth swivel head sealing with grease nipple, welded very strong, bolted and secured central kingpin, bolted wheel axle, zinc-plated.

Top plate drawings: Page 71.
Detailed description: Page 64.

Wheels: HTH/ALTH/GTH Series - Treads: Made of Blickle Extrathane® polyurethane, firmly bonded, colour light brown, non-marking, 92° shore A, elastic, abrasion-resistant, high cut and tear propagation resistance, non-staining, floor-saving, low-noise operation, low rolling resistance, very good chemical connection with the wheel centre. Wheel centres: HTH series: Tubular steel. ALTH series: Aluminium die-cast. GTH series: Grey cast iron, very rugged. Detailed description: Page 44, 45 and 53.

Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LOD-HTH 75K	BOD-HTH 75K	75	2 x 40	500	Ball bearing	123	110 x 140*	75-80 x 105	11	40
LOD-ALTH 101K	BOD-ALTH 101K	100	2 x 40	600	Ball bearing	145	110 x 140*	75-80 x 105	11	45
LOD-GTH 125K	BOD-GTH 125K	125	2 x 40	800	Ball bearing	170	110 x 140*	75-80 x 105	11	50

* Fixed castors: Long plate side in parallel with the wheel axle



Variants / Accessories

	Antistatic version, non-marking grey
Technical description page	44
Ref. No. extension	-AS
Available for wheel Ø [mm]	Upon request