

Series: LE-PO, BE-PO, B-PO

Pressed steel swivel and fixed castors

150 - 300 kg



Brackets: LE/BE/B Series - Pressed steel, swivel bracket with double ball bearing in the swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, with swivel head sealing, bolted wheel axle, zinc-plated.

Top plate drawings: Page 71.
Detailed description: Page 62 and 76.


Wheels: PO Series - Made of high-quality nylon, colour natural white, high abrasion resistance, low rolling resistance, smooth running performance on even floors, shock and impact-resistant, corrosion-resistant, high chemical resistance to alcohol, salts, greases and certain acids and lyes in diluted concentration, plain, roller or ball bearing.

Detailed description: Page 240, 241 and 47.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LE-PO 60G			60	29	150	Plain bearing	80	100 x 85	80 x 60	9	35
LE-PO 75G	B-PO 75G	LE-PO 75G-FI	75	32	150	Plain bearing	100	100 x 85	80 x 60	9	38
LE-PO 75R	B-PO 75R	LE-PO 75R-FI	75	32	150	Roller bearing	100	100 x 85	80 x 60	9	38
LE-PO 80G	B-PO 80G	LE-PO 80G-FI	80	33	150	Plain bearing	102	100 x 85	80 x 60	9	38
LE-PO 80R	B-PO 80R	LE-PO 80R-FI	80	33	150	Roller bearing	102	100 x 85	80 x 60	9	38
LE-PO 100G	BE-PO 100G	LE-PO 100G-FI	100	37	150	Plain bearing	125	100 x 85	80 x 60	9	36
LE-PO 100R	BE-PO 100R	LE-PO 100R-FI	100	37	150	Roller bearing	125	100 x 85	80 x 60	9	36
LE-PO 100K	BE-PO 100K	LE-PO 100K-FI	100	37	150	Ball bearing	125	100 x 85	80 x 60	9	36
LE-PO 125G	BE-PO 125G	LE-PO 125G-FI	125	40	150	Plain bearing	150	100 x 85	80 x 60	9	40
LE-PO 125R	BE-PO 125R	LE-PO 125R-FI	125	40	150	Roller bearing	150	100 x 85	80 x 60	9	40
LE-PO 125K	BE-PO 125K	LE-PO 125K-FI	125	40	150	Ball bearing	150	100 x 85	80 x 60	9	40
LE-PO 150G	B-PO 150G	LE-PO 150G-FI	150	50	300	Plain bearing	190	140 x 110	105 x 75-80	11	54
LE-PO 150R	B-PO 150R	LE-PO 150R-FI	150	50	300	Roller bearing	190	140 x 110	105 x 75-80	11	54
LE-PO 160G	B-PO 160G	LE-PO 160G-FI	160	50	300	Plain bearing	195	140 x 110	105 x 75-80	11	54
LE-PO 160R	B-PO 160R	LE-PO 160R-FI	160	50	300	Roller bearing	195	140 x 110	105 x 75-80	11	54
LE-PO 175G	B-PO 175G	LE-PO 175G-FI	175	50	300	Plain bearing	213	140 x 110	105 x 75-80	11	54
LE-PO 175R	B-PO 175R	LE-PO 175R-FI	175	50	300	Roller bearing	213	140 x 110	105 x 75-80	11	54
LE-PO 200G	B-PO 200G	LE-PO 200G-FI	200	50	300	Plain bearing	235	140 x 110	105 x 75-80	11	54
LE-PO 200R	B-PO 200R	LE-PO 200R-FI	200	50	300	Roller bearing	235	140 x 110	105 x 75-80	11	54

13

Further information on the internet: www.blickle.de



Variants / Accessories

	With pressed steel thread guard, zinc-plated	With "stop-top" brake	With directional lock (retro fit)* 1 x 360°	With bearing seal for ball bearings
Technical description page	79	77	78	58
Ref. No. extension	-FA	-ST	RI-03.03	-KD
Available for wheel Ø [mm]	75 - 200	150 - 200	150 - 200	100 + 125

* Only for swivel castors without brake.