

Series: LEZ-PO

Pressed steel swivel castors with stem fitting

 150 - 270 kg



Brackets: LEZ Series - Pressed steel, with steel stems, with double ball bearing in the swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, bolted wheel axle, zinc-plated.
Detailed description: Page 62 and 76.

Wheels: PO Series - Made of high-quality nylon, colour natural white, high abrasion resistance, low rolling resistance, smooth running performance on even floors, shock and impact-resistant, corrosion-resistant, high chemical resistance to alcohol, salts, greases and certain acids and lyes in diluted concentration, plain bearing.
Detailed description: Page 240, 241 and 47.

Swivel castors		Swivel castors with "stop-fix" brake		Wheel Ø	Wheel width	Load capacity	Bearing version	Total height	Stem Ø	Stem length	Offset
Ref. No.	Ref. No.	[mm]	[mm]	[kg]				[mm]	[mm]	[mm]	[mm]
LEZ-PO 75G	LEZ-PO 75G-FI	75	32	150	Plain bearing	100	20	50	38		
LEZ-PO 80G	LEZ-PO 80G-FI	80	33	150	Plain bearing	102	20	50	38		
LEZ-PO 100G	LEZ-PO 100G-FI	100	37	150	Plain bearing	125	20	50	36		
LEZ-PO 125G	LEZ-PO 125G-FI	125	40	150	Plain bearing	150	20	50	40		
LEZ-PO 150G-22	LEZ-PO 150G-22-FI	150	50	270	Plain bearing	190	22	60	54		
LEZ-PO 150G-27	LEZ-PO 150G-27-FI	150	50	270	Plain bearing	190	27	60	54		
LEZ-PO 160G-22	LEZ-PO 160G-22-FI	160	50	270	Plain bearing	195	22	60	54		
LEZ-PO 160G-27	LEZ-PO 160G-27-FI	160	50	270	Plain bearing	195	27	60	54		
LEZ-PO 200G-22	LEZ-PO 200G-22-FI	200	50	270	Plain bearing	235	22	60	54		
LEZ-PO 200G-27	LEZ-PO 200G-27-FI	200	50	270	Plain bearing	235	27	60	54		

13

Further information on the internet: www.blickle.de

Variants / Accessories



With pressed steel thread guard, zinc-plated

Technical description page	79
Ref. No. extension	-FA
Available for wheel Ø [mm]	All sizes