

Series: LE-POW, BE-POW

**Pressed steel swivel and fixed castors**


 150 kg



**Brackets:** LE/BE Series - Pressed steel, swivel bracket with double ball bearing in the swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, with swivel head sealing, bolted wheel axle, zinc-plated.  
Top plate drawings: Page 71.  
Detailed description: Page 62 and 76.

**Wheels:** POW Series - Treads: Made of high-quality nylon, colour natural white, **noise-absorbing (-10 decibel) achieved with elastic solid rubber inner cushion ring layer**, colour grey, vibration-cushioned operational comfort, high abrasion resistance, low rolling resistance, smooth running performance on even floors, shock and impact-resistant, corrosion-resistant.  
Wheel centres: Made of high-quality nylon, colour black, shock and impact-proof, corrosion-resistant, ball bearing.  
Detailed description: Page 250 and 47.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
Ref. No.	Ref. No.	Ref. No.									
LE-POW 100R	BE-POW 100R	LE-POW 100R-FI	100	35	150	Roller bearing	125	100 x 85	80 x 60	9	36
LE-POW 125R	BE-POW 125R	LE-POW 125R-FI	125	35	150	Roller bearing	150	100 x 85	80 x 60	9	40



**Variants / Accessories**

	With stainless steel roller bearing in the wheel hub
Technical description page	57
Ref. No. extension	-XR
Available for wheel Ø [mm]	Upon request