

Series: LER-POW

Pressed steel swivel castors with bolt hole fitting

 150 kg



Brackets: LER Series - Pressed steel, with bolt hole, double ball bearing in the swivel head and strong central kingpin, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, bolted wheel axle, zinc-plated.
Detailed description: Page 62 and 76.

Wheels: POW Series - Treads: Made of high-quality nylon, colour natural white, **noise-absorbing (-10 decibel) achieved with elastic solid rubber inner cushion ring layer**, colour grey, vibration-cushioned operational comfort, high abrasion resistance, low rolling resistance, smooth running performance on even floors, shock and impact-resistant, corrosion-resistant.
Wheel centres: Made of high-quality nylon, colour black, shock and impact-proof, corrosion-resistant, ball bearing.
Detailed description: Page 250 and 47.

Swivel castors	Swivel castors with "stop-fix" brake
----------------	--------------------------------------

Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset [mm]
LER-POW 100R	LER-POW 100R-FI	100	35	150	Roller bearing	125	70	13	36
LER-POW 125R	LER-POW 125R-FI	125	35	150	Roller bearing	150	70	13	40



13

Further information on the internet: www.blickle.de

Variants / Accessories

	With stainless steel roller bearing in the wheel hub
Technical description page	57
Ref. No. extension	-XR
Available for wheel Ø [mm]	Upon request