

Series: L-POW, B-POW

**Pressed steel swivel and fixed castors,
medium duty brackets**

 180 - 200 kg



Brackets: L/B Series - Pressed steel, swivel bracket with double ball bearing in the reinforced swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, swivel head sealing, bolted wheel axle, zinc-plated.

Top plate drawings: Page 71.
Detailed description: Page 62 and 76.


Wheels: POW Series - Treads: Made of high-quality nylon, colour natural white, **noise-absorbing (-10 decibel)** achieved with **elastic solid rubber inner cushion ring layer**, colour grey, vibration-cushioned operational comfort, high abrasion resistance, low rolling resistance, smooth running performance on even floors, shock and impact-resistant, corrosion-resistant.
Wheel centres: Made of high-quality nylon, colour black, shock and impact-proof, corrosion-resistant, ball bearing.
Detailed description: Page 250 and 47.

Swivel castors

Fixed castors

**Swivel castors
with "stop-fix"
brake**

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
L-POW 100R	B-POW 100R	L-POW 100R-FI	100	35	180	Roller bearing	125	100 x 85	80 x 60	9	36
L-POW 125R	B-POW 125R	L-POW 125R-FI	125	35	200	Roller bearing	150	100 x 85	80 x 60	9	40
L-POW 125K	B-POW 125K	L-POW 125K-FI	125	35	200	Ball bearing	150	100 x 85	80 x 60	9	40



Variants / Accessories

	With stainless steel roller bearing in the wheel hub
Technical description page	57
Ref. No. extension	-XR
Available for wheel Ø [mm]	Upon request