

Series: LK-POW, BK-POW

**Pressed steel swivel and fixed castors,
medium heavy duty brackets**

 180 - 220 kg



Brackets: LK/BK Series - Pressed from heavy sheet-steel, swivel bracket with double ball bearing in the swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, swivel head sealing, bolted wheel axle, zinc-plated.


Top plate drawings: Page 71.
Detailed description: Page 63 and 76.

Wheels: POW Series - Treads: Made of high-quality nylon, colour natural white, **noise-absorbing (-10 decibel) achieved with elastic solid rubber inner cushion ring layer**, colour grey, vibration-cushioned operational comfort, high abrasion resistance, low rolling resistance, smooth running performance on even floors, shock and impact-resistant, corrosion-resistant.

Wheel centres: Made of high-quality nylon, colour black, shock and impact-proof, corrosion-resistant, ball bearing.

Detailed description: Page 250 and 47.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
Ref. No.	Ref. No.	Ref. No.									
LK-POW 100R-1	BK-POW 100R-1	LK-POW 100R-1-FI	100	35	180	Roller bearing	130	100 x 85	80 x 60	9	45
LK-POW 100R-3	BK-POW 100R-3	LK-POW 100R-3-FI	100	35	180	Roller bearing	130	140 x 110	105 x 75-80	11	45
LK-POW 125R-1	BK-POW 125R-1	LK-POW 125R-1-FI	125	35	220	Roller bearing	155	100 x 85	80 x 60	9	48
LK-POW 125R-3	BK-POW 125R-3	LK-POW 125R-3-FI	125	35	220	Roller bearing	155	140 x 110	105 x 75-80	11	48
LK-POW 125K-1	BK-POW 125K-1	LK-POW 125K-1-FI	125	35	220	Ball bearing	155	100 x 85	80 x 60	9	48
LK-POW 125K-3	BK-POW 125K-3	LK-POW 125K-3-FI	125	35	220	Ball bearing	155	140 x 110	105 x 75-80	11	48



13

Further information on the internet: www.blickle.de

Variants / Accessories

	With stainless steel roller bearing in the wheel hub
Technical description page	57
Ref. No. extension	-XR
Available for wheel Ø [mm]	Upon request