


Series: L-PP, B-PP

Pressed steel swivel and fixed castors, medium heavy brackets

 120 - 400 kg



Brackets: L/B Series - Pressed steel, swivel bracket with double ball bearing in the reinforced swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, strong central kingpin (wheel Ø 150+200 mm) and swivel head sealing, bolted wheel axle, zinc-plated.

Wheels: PP Series - Made of polypropylene, colour black, shock and impact-resistant, corrosion-resistant, plain or roller bearing.

Detailed description: Page 255 and 46.

Top plate drawings: Page 71.
Detailed description: Page 62 and 76.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
L-PP 80G	B-PP 80G	L-PP 80G-FI	80	33	120	Plain bearing	102	100 x 85	80 x 60	9	38
L-PP 80R	B-PP 80R	L-PP 80R-FI	80	33	120	Roller bearing	102	100 x 85	80 x 60	9	38
L-PP 100G	B-PP 100G	L-PP 100G-FI	100	37	160	Plain bearing	125	100 x 85	80 x 60	9	36
L-PP 100R	B-PP 100R	L-PP 100R-FI	100	37	160	Roller bearing	125	100 x 85	80 x 60	9	36
L-PP 125G	B-PP 125G	L-PP 125G-FI	125	40	200	Plain bearing	150	100 x 85	80 x 60	9	40
L-PP 125R	B-PP 125R	L-PP 125R-FI	125	40	200	Roller bearing	150	100 x 85	80 x 60	9	40
L-PP 150G	B-PP 150G	L-PP 150G-FI	150	50	300	Plain bearing	190	140 x 110	105 x 75-80	11	60
L-PP 150R	B-PP 150R	L-PP 150R-FI	150	50	300	Roller bearing	190	140 x 110	105 x 75-80	11	60
L-PP 200G	B-PP 200G	L-PP 200G-FI	200	50	400	Plain bearing	235	140 x 110	105 x 75-80	11	65
L-PP 200R	B-PP 200R	L-PP 200R-FI	200	50	400	Roller bearing	235	140 x 110	105 x 75-80	11	65

13



Further information on the internet: www.blickle.de

Variants / Accessories



	With pressed steel thread guard, zinc-plated	With "stop-top" brake	With directional lock (retro fit)* 1 x 360°
Technical description page	79	77	78
Ref. No. extension	-FA	-ST	RI-05.03
Available for wheel Ø [mm]	All sizes	All sizes	150 + 200

* Only for swivel castors without brake.