

Series: LKR-SPO

Pressed steel swivel castors with bolt hole fitting, medium heavy duty brackets

 250 kg



Brackets: LKR Series - Pressed from heavy sheet-steel, single bolt hole fitting, double ball bearing in the swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, strong central kingpin, bolted wheel axle, zinc-plated.
Detailed description: Page 63 and 76.

Wheels: SPO Series - Made of high-quality nylon, very rugged, colour natural white, high abrasion resistance, low rolling resistance, smooth running performance on even floors, shock and impact-resistant, corrosion-resistant, high chemical resistance to alcohol, salts, greases and certain acids and lyes in diluted concentration, plain or ball bearing.
Detailed description: Page 262 and 47.

Swivel castors		Swivel castors with "stop-fix" brake		Wheel Ø	Wheel width	Load capacity	Bearing version	Total height	Plate Ø	Bolt hole Ø	Offset
Ref. No.	Ref. No.	[mm]	[mm]	[kg]	[mm]	[mm]		[mm]	[mm]	[mm]	[mm]
LKR-SPO 75G		75	32	250	Plain bearing	108	88	13	40		
LKR-SPO 75K		75	32	250	Ball bearing	108	88	13	40		
LKR-SPO 100G	LKR-SPO 100G-FI	100	37	250	Plain bearing	130	88	13	45		
LKR-SPO 100K	LKR-SPO 100K-FI	100	37	250	Ball bearing	130	88	13	45		
LKR-SPO 125G	LKR-SPO 125G-FI	125	40	250	Plain bearing	155	88	13	48		
LKR-SPO 125K	LKR-SPO 125K-FI	125	40	250	Ball bearing	155	88	13	48		



Variants / Accessories

	With pressed steel thread guard, zinc-plated	With stainless steel axle tube in the wheel hub	With stainless steel ball bearing in the wheel hub
Technical description page	79	79	57
Ref. No. extension	-FA	-XA	-XK
Available for wheel Ø [mm]	All sizes	All plain bearing versions	Upon request