


Series: LT-SPO, BT-SPO

Malleable cast iron swivel and fixed castors

 300 - 750 kg



Brackets: LT/BT Series - Made of high-quality white malleable cast iron, swivel bracket with double ball bearing in the swivel head (wheel Ø 75 mm with single ball bearing), swivel head with ball protection, fitted grease nipple, bolted wheel axle, zinc-plated.
Top plate drawings: Page 73.
Detailed description: Page 63.

Wheels: SPO Series - Made of high-quality nylon, very rugged, colour natural white, high abrasion resistance, low rolling resistance, smooth running performance on even floors, shock and impact-resistant, corrosion-resistant, high chemical resistance to alcohol, salts, greases and certain acids and lyes in diluted concentration, plain bearing.
Detailed description: Page 262 and 47.

Swivel castors	Fixed castors
----------------	---------------

Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LT-SPO 75G	BT-SPO 75G	75	32	300	Plain bearing	108	115 x 80	90 x 55	9	30
LT-SPO 100G	BT-SPO 100G	100	37	500	Plain bearing	150	155 x 105	125 x 75	11	40
LT-SPO 125G	BT-SPO 125G	125	40	500	Plain bearing	163	155 x 105	125 x 75	11	40
LT-SPO 150G	BT-SPO 150G	150	50	750	Plain bearing	200	175 x 125	145 x 95	11	50

