

Series: G
Cast iron wheels

 200 - 1400 kg



Made of grey cast iron, very rugged, machined tread and tread edges, high abrasion resistance, low rolling resistance, insensitive to metal swarf, grease nipple, plain, roller or ball bearing, temperature range from -30° to +140°C. For application in temperatures exceeding +140°C, refer to page 343. Lacquered - colour silver. Detailed description: Page 49.

Wheels


Plain bearing versions must be regularly lubricated.

Ref. No.	Wheel Ø (D) [mm]	Wheel width (T2) [mm]	Load capacity [kg]	Bearing version	Axle bore Ø (d) [mm]	Hub length (T1) [mm]
G 80/12G	80	25	250	Plain bearing	12	35
G 80/12R	80	25	200	Roller bearing	12	35
G 100/15G	100	35	400	Plain bearing	15	45
G 100/15R	100	35	250	Roller bearing	15	45
G 125/15G	125	35	450	Plain bearing	15	45
G 125/15R	125	35	250	Roller bearing	15	45
G 127/20G	125	50	750	Plain bearing	20	60
G 127/20K	125	50	750	Ball bearing	20	60
G 150/20G	150	50	900	Plain bearing	20	60
G 150/20R	150	50	600	Roller bearing	20	60
G 150/20K	150	50	900	Ball bearing	20	60
G 200/20G	200	50	1100	Plain bearing	20	60
G 200/20R	200	50	600	Roller bearing	20	60
G 200/20K	200	50	1100	Ball bearing	20	60
G 250/25G	250	60	1400	Plain bearing	25	65
G 250/25K	250	60	1400	Ball bearing	25	70

15

Further information on the internet: www.blickle.de

Variants / Accessories



Heat-resistant versions

Technical description page

Ref. No. extension

Available for wheel Ø [mm] Refer to page 343.

