

Series: L-G, B-G, BH-G

Pressed steel swivel and fixed castors, medium duty brackets

200 - 600 kg



Brackets: L/B/BH Series - Pressed steel, swivel bracket with double ball bearing in the reinforced swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, strong central kingpin (wheel Ø 150-250 mm) and swivel head sealing, bolted wheel axle, zinc-plated.

Top plate drawings: Page 71.
Detailed description: Page 62 and 76.

Wheels: G Series - Made of grey cast iron, very rugged, machined tread and tread edges, high abrasion resistance, low rolling resistance, insensitive to metal swarf, grease nipple, plain or ball bearing (regular lubrication required).
Lacquered - colour silver.
Detailed description: Page 278 and 49.

Temperature range from -30°C to +70°C.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake
----------------	---------------	--------------------------------------

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
L-G 80G	B-G 80G	L-G 80G-FI	80	25	200	Plain bearing	102	100 x 85	80 x 60	9	38
L-G 100G	B-G 100G	L-G 100G-FI	100	35	200	Plain bearing	125	100 x 85	80 x 60	9	36
L-G 125G	B-G 125G	L-G 125G-FI	125	35	200	Plain bearing	150	100 x 85	80 x 60	9	40
L-G 150G	B-G 150G	L-G 150G-FI	150	50	400	Plain bearing	190	140 x 110	105 x 75-80	11	60
L-G 200G	B-G 200G	L-G 200G-FI	200	50	400	Plain bearing	235	140 x 110	105 x 75-80	11	65
L-G 250G-3	BH-G 250G	*	250	60	600	Plain bearing	295	140 x 110	105 x 75-80	11	77

* For the "stop-top" brake version, refer to Variants / Accessories.



Variants / Accessories



	With "stop-top" brake	With directional lock (retro fit)** 1 x 360°	Heat-resistant versions
Technical description page	77	78	
Ref. No. extension	-ST	RI-05.03	
Available for wheel Ø [mm]	All sizes	150 + 200	Refer to page 344.

** Only for swivel castors without brake.