

Series: LK-G, BK-G, BH-G

**Pressed steel swivel and fixed castors, medium heavy duty brackets**

250 - 600 kg



**Brackets:** LK/BK/BH Series - Pressed from heavy sheet-steel, swivel bracket with double ball bearing in the reinforced swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely low swivel head play and a long service life, strong central kingpin (wheel Ø 125x54 - 200 mm) and swivel head sealing, bolted wheel axle, zinc-plated.

Top plate drawings: Page 71.  
Detailed description: Page 63 and 76.


**Wheels:** G Series - Made of grey cast iron, very rugged, machined tread and tread edges, high abrasion resistance, low rolling resistance, insensitive to metal swarf, grease nipple, plain or ball bearing.  
Lacquered - colour silver.  
Detailed description: Page 278 and 49

Plain bearing versions must be regularly lubricated.

Temperature range from **-30°C to +70°C**.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
Ref. No.	Ref. No.	Ref. No.									
LK-G 80G	BK-G 80G	*	80	25	250	Plain bearing	110	100 x 85	80 x 60	9	40
LK-G 100G-1	BK-G 100G-1	LK-G 100G-1-FI	100	35	250	Plain bearing	130	100 x 85	80 x 60	9	45
LK-G 100G-3	BK-G 100G-3	LK-G 100G-3-FI	100	35	250	Plain bearing	130	140 x 110	105 x 75-80	11	45
LK-G 125G-1	BK-G 125G-1	LK-G 125G-1-FI	125	35	250	Plain bearing	155	100 x 85	80 x 60	9	48
LK-G 125G-3	BK-G 125G-3	LK-G 125G-3-FI	125	35	250	Plain bearing	155	140 x 110	105 x 75-80	11	48
LK-G 127G	BH-G 127G	LK-G 127G-FI	125	50	600	Plain bearing	170	140 x 110	105 x 75-80	11	55
LK-G 127K	BH-G 127K	LK-G 127K-FI	125	50	600	Ball bearing	170	140 x 110	105 x 75-80	11	55
LK-G 150G	BH-G 150G	LK-G 150G-FI	150	50	600	Plain bearing	197	140 x 110	105 x 75-80	11	63
LK-G 150K	BH-G 150K	LK-G 150K-FI	150	50	600	Ball bearing	197	140 x 110	105 x 75-80	11	63
LK-G 200G	BH-G 200G	LK-G 200G-FI	200	50	600	Plain bearing	245	140 x 110	105 x 75-80	11	65
LK-G 200K	BH-G 200K	LK-G 200K-FI	200	50	600	Ball bearing	245	140 x 110	105 x 75-80	11	65

\* For the "stop-top" brake version, refer to Variants / Accessories.



15

Further information on the internet: [www.blickle.de](http://www.blickle.de)



**Variants / Accessories**

	With "stop-top" brake	With directional lock (retro fit)** 1 x 360°	With directional lock (retro fit)** 1 x 360°
Technical description page	77	78	78
Ref. No. extension	-ST	RI-03.03	RI-05.03
Available for wheel Ø [mm]	All sizes	100 + 125 plate 140x110	125x50 - 200

\*\* Only for swivel castors without brake.