

Series: LS-G, BS-G

Welded steel heavy duty swivel and fixed castors, extra strong swivel head design

750 - 1400 kg



Brackets: LS/BS Series - Very rugged welded steel construction, swivel bracket with axial grooved ball bearing DIN 711 and tapered roller bearing DIN 720 in the swivel head, dust and splash-proof. Fitted grease nipple, welded very strong, bolted and secured central kingpin, bolted wheel axle, zinc-plated - yellow passivated.
Top plate drawings: Page 71 and 72.
Detailed description: Page 64 and 77.


Wheels: G Series - Made of grey cast iron, very rugged, machined tread and tread edges, high abrasion resistance, low rolling resistance, insensitive to metal swarf, grease nipple, plain or ball bearing.
Lacquered - colour silver.
Detailed description: Page 278 and 49.

Plain bearing versions must be regularly lubricated.

Temperature range from -30°C to +100°C.

Swivel castors	Fixed castors	Swivel castors with "stop-top" brake
----------------	---------------	--------------------------------------

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LS-G 127G	BS-G 127G	LS-G 127G-ST	125	50	750	Plain bearing	170	140 x 110	105 x 75-80	11	50
LS-G 127K	BS-G 127K	LS-G 127K-ST	125	50	750	Ball bearing	170	140 x 110	105 x 75-80	11	50
LS-G 150G	BS-G 150G	LS-G 150G-ST	150	50	900	Plain bearing	200	140 x 110	105 x 75-80	11	55
LS-G 150K	BS-G 150K	LS-G 150K-ST	150	50	900	Ball bearing	200	140 x 110	105 x 75-80	11	55
LS-G 200G	BS-G 200G	LS-G 200G-ST	200	50	1100	Plain bearing	245	140 x 110	105 x 75-80	11	60
LS-G 200K	BS-G 200K	LS-G 200K-ST	200	50	1100	Ball bearing	245	140 x 110	105 x 75-80	11	60
LS-G 250G	BS-G 250G	LS-G 250G-ST	250	60	1400	Plain bearing	305	175 x 140	140 x 105	14	75
LS-G 250K	BS-G 250K	LS-G 250K-ST	250	60	1400	Ball bearing	305	175 x 140	140 x 105	14	75



15

Further information on the internet: www.blickle.de

Variants / Accessories



	With directional lock 2 x 180°	With directional lock 4 x 90°
Technical description page	78	78
Ref. No. extension	-RI2	-RI4
Available for wheel Ø [mm]	All sizes	Upon request