

Series: LKRXA-PTH, BKRXA-PTH

**Stainless steel light duty swivel and fixed castors with bolt hole fitting**


**120 kg**



**Brackets:** LKRXA/BKRXA Series - Pressed from high-quality, chromium-nickel stainless steel (material No. 1.4301/AISI 304), swivel bracket with double ball bearing in the swivel head, strong central kingpin and bolted wheel axle. All metal parts are stainless steel and brackets are vibration-ground finished.  
Detailed description: Page 67 and 76.

**Wheels:** PTH Series - Treads: Made of injection-moulded polyurethane, colour grey, non-marking, 98° shore A, abrasion-resistant, non-staining, floor-saving, low-noise operation, low rolling resistance, excellent positive and non-positive connection with the wheel centre.  
Wheel centres: Made of high-quality nylon, colour light grey, shock and impact-resistant, corrosion-resistant, plain bearing.  
Detailed description: Page 102 and 32.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LKRXA-PTH 80G	BKRXA-PTH 80G	LKRXA-PTH 80G-FI	80	30	120	Plain bearing	108	57	13	40
LKRXA-PTH 80G-11		LKRXA-PTH 80G-11-FI	80	30	120	Plain bearing	108	57	11	40
LKRXA-PTH 101G	BKRXA-PTH 101G	LKRXA-PTH 101G-FI	100	30	120	Plain bearing	133	57	13	40
LKRXA-PTH 101G-11		LKRXA-PTH 101G-11-FI	100	30	120	Plain bearing	133	57	11	40
LKRXA-PTH 126G	BKRXA-PTH 126G	LKRXA-PTH 126G-FI	125	30	120	Plain bearing	158	57	13	40
LKRXA-PTH 126G-11		LKRXA-PTH 126G-11-FI	125	30	120	Plain bearing	158	57	11	40



18



Antistatic version, non-marking grey

**Variants / Accessories**

Technical description page	32
Ref. No. extension	-ELS
Available for wheel Ø [mm]	Upon request