

Series: LKPXA-PTH, BKPXA-PTH

Stainless steel light duty swivel and fixed castors

 120 kg




Brackets: LKPXA/BKPXA Series - Pressed from high-quality, chromium-nickel stainless steel (material No. 1.4301/AISI 304), swivel bracket with double ball bearing in the swivel head, strong central kingpin and bolted wheel axle. All metal parts are stainless steel and brackets are vibration-ground finished. Top plate drawings: Page 70. Detailed description: Page 67 and 76.

Wheels: PTH Series - Treads: Made of injection-moulded polyurethane, colour grey, non-marking, 98° shore A, abrasion-resistant, non-staining, floor-saving, low-noise operation, low rolling resistance, excellent positive and non-positive connection with the wheel centre. Wheel centres: Made of high-quality nylon, colour light grey, shock and impact-resistant, corrosion-resistant, plain bearing. Detailed description: Page 102 and 32.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake
----------------	---------------	--------------------------------------

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LKPXA-PTH 80G	BKPXA-PTH 80G	LKPXA-PTH 80G-FI	80	30	120	Plain bearing	111	90 x 66	75x45/61x51	8,5	40
LKPXA-PTH 101G	BKPXA-PTH 101G	LKPXA-PTH 101G-FI	100	30	120	Plain bearing	136	90 x 66	75x45/61x51	8,5	40
LKPXA-PTH 126G	BKPXA-PTH 126G	LKPXA-PTH 126G-FI	125	30	120	Plain bearing	161	90 x 66	75x45/61x51	8,5	40



Variants / Accessories

	Antistatic version, non-marking grey
Technical description page	32
Ref. No. extension	-ELS
Available for wheel Ø [mm]	Upon request