

Series: LEXR-VPP

**Stainless steel swivel castors with bolt hole fitting**

 50 - 205 kg



**Brackets:** LEXR Series - Pressed from high-quality, chromium-nickel stainless steel (material No. 1.4301/AISI 304), swivel bracket with double ball bearing in the swivel head, strong central kingpin, bolted wheel axle. All metal parts are stainless steel and brackets are vibration-ground finished.  
Detailed description: Page 68 and 76.

**Wheels:** VPP Series - Tyres: Solid rubber, colour grey, non-marking, 80° shore A or 90° shore A with wheel dimensions of 80x32 mm.  
**Rims:** Made of polypropylene, shock and impact-resistant, corrosion-resistant, plain bearing, colour black.  
Detailed description: Page 133, 134 and 34.

Swivel castors	Swivel castors with "stop-fix" brake
----------------	--------------------------------------

Ref. No.	Ref. No.	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset [mm]
LEXR-VPP 80G-SG	LEXR-VPP 80G-SG-FI	80	25	50	Plain bearing	102	70	13	38
LEXR-VPP 82G-SG	LEXR-VPP 82G-SG-FI	80	32	100	Plain bearing	102	70	13	38
LEXR-VPP 100G-SG	LEXR-VPP 100G-SG-FI	100	30	70	Plain bearing	125	70	13	36
LEXR-VPP 125G-SG	LEXR-VPP 125G-SG-FI	125	37,5	100	Plain bearing	150	70	13	40
LEXR-VPP 150G-SG	LEXR-VPP 150G-SG-FI	150	40	135	Plain bearing	190	88	13	54
LEXR-VPP 160G-SG	LEXR-VPP 160G-SG-FI	160	40	135	Plain bearing	195	88	13	54
LEXR-VPP 200G-SG	LEXR-VPP 200G-SG-FI	200	50	205	Plain bearing	235	88	13	54

