

Series: LEXZ-VPP

Stainless steel swivel castors with stem fitting

 50 - 205 kg



Brackets: LEXZ Series - Pressed from high-quality, chromium-nickel stainless steel (material No. 1.4301/AISI 304), swivel bracket with double ball bearing in the swivel head, plug-in stem, bolted wheel axle. All metal parts are stainless steel and brackets are vibration-ground finished.
Detailed description: Page 68 and 76.

Wheels: VPP Series - Tyres: Solid rubber, colour grey, non-marking, 80° shore A or 90° shore A with wheel dimensions of 80x32 mm.
Rims: Made of polypropylene, shock and impact-resistant, corrosion-resistant, plain bearing, colour black.
Detailed description: Page 133, 134 and 34.

Swivel castors		Swivel castors with "stop-fix" brake		Wheel Ø	Tyre width	Load capacity	Bearing version	Total height	Stem Ø	Stem length	Offset
Ref. No.	Ref. No.	[mm]	[mm]	[mm]	[mm]	[kg]		[mm]	[mm]	[mm]	[mm]
LEXZ-VPP 80G-SG	LEXZ-VPP 80G-SG-FI	80	25	50	Plain bearing	102	20	50	38		
LEXZ-VPP 82G-SG	LEXZ-VPP 82G-SG-FI	80	32	100	Plain bearing	102	20	50	38		
LEXZ-VPP 100G-SG	LEXZ-VPP 100G-SG-FI	100	30	70	Plain bearing	125	20	50	36		
LEXZ-VPP 125G-SG	LEXZ-VPP 125G-SG-FI	125	37,5	100	Plain bearing	150	20	50	40		
LEXZ-VPP 150G-SG	LEXZ-VPP 150G-SG-FI	150	40	135	Plain bearing	190	27	60	54		
LEXZ-VPP 160G-SG	LEXZ-VPP 160G-SG-FI	160	40	135	Plain bearing	195	27	60	54		
LEXZ-VPP 200G-SG	LEXZ-VPP 200G-SG-FI	200	50	205	Plain bearing	235	27	60	54		

