

Series: LEXR-PTH

Stainless steel swivel castors with bolt hole fitting

 125 - 300 kg



Brackets: LEXR Series - Pressed from high-quality, chromium-nickel stainless steel (material No. 1.4301/AISI 304), with double ball bearing in the swivel head, with strong central kingpin, bolted wheel axle. All metal parts are stainless steel and brackets are vibration-ground finished.
Detailed description: Page 68 and 76.

Wheels: PTH Series - Treads: Made of injection-moulded polyurethane, colour grey, non-marking, 98° shore A, abrasion-resistant, non-staining, floor-saving, low-noise operation, low rolling resistance, excellent positive and non-positive connection with the wheel centre. Wheel centres: Made of high-quality nylon, colour light grey, shock and impact-resistant, corrosion-resistant, plain bearing.
Detailed description: Page 198 and 43.

Swivel castors	Swivel castors with "stop-fix" brake	Wheel Ø	Wheel width	Load capacity	Bearing version	Total height	Plate Ø	Bolt hole Ø	Offset
Ref. No.	Ref. No.	[mm]	[mm]	[kg]		[mm]	[mm]	[mm]	[mm]
LEXR-PTH 80G	LEXR-PTH 80G-FI	80	30	125	Plain bearing	102	70	13	38
LEXR-PTH 100G	LEXR-PTH 100G-FI	100	30	150	Plain bearing	125	70	13	36
LEXR-PTH 125G	LEXR-PTH 125G-FI	125	30	150	Plain bearing	150	70	13	40
LEXR-PTH 160G	LEXR-PTH 160G-FI	160	40	300	Plain bearing	195	88	13	54
LEXR-PTH 200G	LEXR-PTH 200G-FI	200	50	300	Plain bearing	235	88	13	54



18

Variants / Accessories



Antistatic version, non-marking grey

Technical description page

43

Ref. No. extension

-ELS

Available for wheel Ø [mm]

Upon request