

Series: LEXZ-PTH

Stainless steel swivel castors with stem fitting


 125 - 270 kg



Brackets: LEXZ Series - Pressed from high-quality, chromium-nickel stainless steel (material No. 1.4301/AISI 304), swivel bracket with double ball bearing in the swivel head, plug-in stem, bolted wheel axle. All metal parts are stainless steel and brackets are vibration-ground finished. Detailed description: Page 68 and 76.

Wheels: PTH Series - Treads: Made of injection-moulded polyurethane, colour grey, non-marking, 98° shore A, abrasion-resistant, non-staining, floor-saving, low-noise operation, low rolling resistance, excellent positive and non-positive connection with the wheel centre. Wheel centres: Made of high-quality nylon, colour light grey, shock and impact-resistant, corrosion-resistant, plain bearing. Detailed description: Page 198 and 43.

Swivel castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Stem Ø [mm]	Stem length [mm]	Offset [mm]
LEXZ-PTH 80G	LEXZ-PTH 80G-FI	80	30	125	Plain bearing	102	20	50	38
LEXZ-PTH 100G	LEXZ-PTH 100G-FI	100	30	150	Plain bearing	125	20	50	36
LEXZ-PTH 125G	LEXZ-PTH 125G-FI	125	30	150	Plain bearing	150	20	50	40
LEXZ-PTH 160G	LEXZ-PTH 160G-FI	160	40	270	Plain bearing	195	27	60	54
LEXZ-PTH 200G	LEXZ-PTH 200G-FI	200	50	270	Plain bearing	235	27	60	54



Variants / Accessories

Antistatic version, non-marking grey

Technical description page

43

Ref. No. extension

-ELS

Available for wheel Ø [mm]

Upon request