

Series: LEX-POTH, BEX-POTH, BX-POTH  
**Stainless steel swivel and fixed castors**

150 - 300 kg




**Brackets:** LEX/BEX/BX Series - Pressed from high-quality, chromium-nickel stainless steel (material No. 1.4301/AISI 304), swivel bracket with double ball bearing in the swivel head, swivel head sealing, bolted wheel axle. All metal parts are stainless steel and brackets are vibration-ground finished. Top plate drawings: Page 71. Detailed description: Page 67 and 76.

**Wheels:** POTH Series - Treads: Made of injection-moulded polyurethane, colour brown, non-marking, 98° shore A, non-staining, abrasion-resistant, floor-saving, low-noise operation, low rolling resistance, excellent positive and non-positive connection with the wheel centre. **Alternatively available with soft tread with improved skid resistance, colour grey, 92° shore A, refer to Variants / Accessories.** Wheel centres: Made of high-quality nylon, colour natural white, shock and impact-resistant, corrosion-resistant, plain or stainless steel roller bearing. Detailed description: Page 202 and 43.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake
----------------	---------------	--------------------------------------

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LEX-POTH 100G	BEX-POTH 100G	LEX-POTH 100G-FI	100	35	150	Plain bearing	125	100 x 85	80 x 60	9	36
LEX-POTH 100XR	BEX-POTH 100XR	LEX-POTH 100XR-FI	100	35	150	Roller bearing	125	100 x 85	80 x 60	9	36
LEX-POTH 125G	BEX-POTH 125G	LEX-POTH 125G-FI	125	35	150	Plain bearing	150	100 x 85	80 x 60	9	40
LEX-POTH 125XR	BEX-POTH 125XR	LEX-POTH 125XR-FI	125	35	150	Roller bearing	150	100 x 85	80 x 60	9	40
LEX-POTH 150G	BX-POTH 150G	LEX-POTH 150G-FI	150	40	300	Plain bearing	190	140 x 110	105 x 75-80	11	54
LEX-POTH 150XR	BX-POTH 150XR	LEX-POTH 150XR-FI	150	40	300	Roller bearing	190	140 x 110	105 x 75-80	11	54
LEX-POTH 200G	BX-POTH 200G	LEX-POTH 200G-FI	200	50	300	Plain bearing	235	140 x 110	105 x 75-80	11	54
LEX-POTH 200XR	BX-POTH 200XR	LEX-POTH 200XR-FI	200	50	300	Roller bearing	235	140 x 110	105 x 75-80	11	54



18

**Variants / Accessories**



	With soft tread, 92° shore A, non-marking grey	With "ideal-stop" brake *
Technical description page	43	77
Ref. No. extension	-WE	-IS
Available for wheel Ø [mm]	Upon request	200

\* Without alteration of the total height.