

Series: LX-POTH, BX-POTH

Stainless steel swivel and fixed castors, medium duty brackets

400 kg




Brackets: LX/BX Series - Pressed from high-quality, chromium-nickel stainless steel (material No. 1.4301/AISI 304), swivel bracket with double ball bearing in the reinforced swivel head, swivel head sealing, strong central kingpin, bolted wheel axle. All metal parts are stainless steel and brackets are vibration-ground finished. Top plate drawings: Page 71. Detailed description: Page 68 and 76.

Wheels: POTH Series - Treads: Made of injection-moulded polyurethane, colour brown, non-marking, 98° shore A, non-staining, abrasion-resistant, floor-saving, low-noise operation, low rolling resistance, excellent positive and non-positive connection with the wheel centre. **Alternatively available with soft tread with improved skid resistance, colour grey, 92° shore A, refer to Variants / Accessories.** Wheel centres: Made of high-quality nylon, colour natural white, shock and impact-resistant, corrosion-resistant, plain, stainless steel roller or ball bearing. Detailed description: Page 202 and 43.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake
----------------	---------------	--------------------------------------

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LX-POTH 150G	BX-POTH 150G	LX-POTH 150G-FI	150	40	400	Plain bearing	190	140 x 110	105 x 75-80	11	60
LX-POTH 150XR	BX-POTH 150XR	LX-POTH 150XR-FI	150	40	400	Roller bearing	190	140 x 110	105 x 75-80	11	60
LX-POTH 150XK	BX-POTH 150XK	LX-POTH 150XK-FI	150	40	400	Ball bearing	190	140 x 110	105 x 75-80	11	60
LX-POTH 200G	BX-POTH 200G	LX-POTH 200G-FI	200	50	400	Plain bearing	235	140 x 110	105 x 75-80	11	65
LX-POTH 200XR	BX-POTH 200XR	LX-POTH 200XR-FI	200	50	400	Roller bearing	235	140 x 110	105 x 75-80	11	65
LX-POTH 200XK	BX-POTH 200XK	LX-POTH 200XK-FI	200	50	400	Ball bearing	235	140 x 110	105 x 75-80	11	65



Variants / Accessories

	With soft tread, 92° shore A, non-marking grey
Technical description page	43
Ref. No. extension	-WE
Available for wheel Ø [mm]	Upon request