

Series: LKX-POTH, BKX-POTH

Stainless steel swivel and fixed castors, heavy duty brackets

250 - 700 kg




Brackets: LKX/BKX Series - Pressed from heavy, high-quality, chromium-nickel stainless steel (material No. 1.4301/AISI 304), reinforced fork and top plate, double ball bearing in the swivel head, swivel head sealing, very strong central kingpin. All metal parts are stainless steel and brackets are vibration-ground finished.
Top plate drawings: Page 71.
Detailed description: Page 68 and 76.

Wheels: POTH Series - Treads: Made of injection-moulded polyurethane, colour brown, non-marking, 98° shore A, non-staining, abrasion-resistant, floor-saving, low-noise operation, low rolling resistance, excellent positive and non-positive connection with the wheel centre.
Alternatively available with soft tread with improved skid resistance, colour grey, 92° shore A, refer to Variants / Accessories.
Wheel centres: Made of high-quality nylon, colour natural white, shock and impact-resistant, corrosion-resistant, plain or stainless steel ball bearing.
Detailed description: Page 202 and 43.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake
----------------	---------------	--------------------------------------

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LKX-POTH 125G	BKX-POTH 125G	*	125	35	250	Plain bearing	165	140 x 110	105 x 75-80	11	55
LKX-POTH 125XK	BKX-POTH 125XK	*	125	35	250	Ball bearing	165	140 x 110	105 x 75-80	11	55
LKX-POTH 150G	BKX-POTH 150G	LKX-POTH 150G-FI	150	40	400	Plain bearing	197	140 x 110	105 x 75-80	11	63
LKX-POTH 150XK	BKX-POTH 150XK	LKX-POTH 150XK-FI	150	40	400	Ball bearing	197	140 x 110	105 x 75-80	11	63
LKX-POTH 200G	BKX-POTH 200G	LKX-POTH 200G-FI	200	50	700	Plain bearing	245	140 x 110	105 x 75-80	11	65
LKX-POTH 200XK	BKX-POTH 200XK	LKX-POTH 200XK-FI	200	50	700	Ball bearing	245	140 x 110	105 x 75-80	11	65

* For the "stop-top" brake version, refer to Variants / Accessories.



18

Further information on the internet: www.blickle.de

Variants / Accessories



	With soft tread, 92° shore A, non-marking grey	With "stop-top" brake
Technical description page	43	77
Ref. No. extension	-WE	-ST
Available for wheel Ø [mm]	Upon request	125