

Series: LEX-PO, BEX-PO, BX-PO

Stainless steel swivel and fixed castors

 150 - 300 kg



Brackets: LEX/BEX/BX Series - Pressed from high-quality, chromium-nickel stainless steel (material No. 1.4301/AISI 304), swivel bracket with double ball bearing in the swivel head, swivel head sealing, bolted wheel axle. All metal parts are stainless steel and brackets are vibration-ground finished.
Top plate drawings: Page 71.
Detailed description: Page 67 and 76.

Wheels: PO Series - Made of high-quality nylon, colour natural white, high abrasion resistance, low rolling resistance, smooth running performance on even floors, shock and impact-resistant, corrosion-resistant, high chemical resistance to alcohol, salts, greases and certain acids and lyes in diluted concentration, plain, stainless steel roller bearing or sealed ball bearing. As standard, ball bearing versions are supplied with bearing sealing.
Detailed description: Page 240, 241 47 and 58.

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LEX-PO 75G	BEX-PO 75G	LEX-PO 75G-FI	75	32	150	Plain bearing	100	100 x 85	80 x 60	9	38
LEX-PO 75XR	BEX-PO 75XR	LEX-PO 75XR-FI	75	32	150	Roller bearing	100	100 x 85	80 x 60	9	38
LEX-PO 80G	BEX-PO 80G	LEX-PO 80G-FI	80	33	150	Plain bearing	102	100 x 85	80 x 60	9	38
LEX-PO 80XR	BEX-PO 80XR	LEX-PO 80XR-FI	80	33	150	Roller bearing	102	100 x 85	80 x 60	9	38
LEX-PO 100G	BEX-PO 100G	LEX-PO 100G-FI	100	37	150	Plain bearing	125	100 x 85	80 x 60	9	36
LEX-PO 100XR	BEX-PO 100XR	LEX-PO 100XR-FI	100	37	150	Roller bearing	125	100 x 85	80 x 60	9	36
LEX-PO 100KD	BEX-PO 100KD	LEX-PO 100KD-FI	100	37	150	Ball bearing	125	100 x 85	80 x 60	9	36
LEX-PO 125G	BEX-PO 125G	LEX-PO 125G-FI	125	40	150	Plain bearing	150	100 x 85	80 x 60	9	40
LEX-PO 125XR	BEX-PO 125XR	LEX-PO 125XR-FI	125	40	150	Roller bearing	150	100 x 85	80 x 60	9	40
LEX-PO 125KD	BEX-PO 125KD	LEX-PO 125KD-FI	125	40	150	Ball bearing	150	100 x 85	80 x 60	9	40
LEX-PO 150G	BX-PO 150G	LEX-PO 150G-FI	150	50	300	Plain bearing	190	140 x 110	105 x 75-80	11	54
LEX-PO 150XR	BX-PO 150XR	LEX-PO 150XR-FI	150	50	300	Roller bearing	190	140 x 110	105 x 75-80	11	54
LEX-PO 160G	BX-PO 160G	LEX-PO 160G-FI	160	50	300	Plain bearing	195	140 x 110	105 x 75-80	11	54
LEX-PO 160XR	BX-PO 160XR	LEX-PO 160XR-FI	160	50	300	Roller bearing	195	140 x 110	105 x 75-80	11	54
LEX-PO 200G	BX-PO 200G	LEX-PO 200G-FI	200	50	300	Plain bearing	235	140 x 110	105 x 75-80	11	54
LEX-PO 200XR	BX-PO 200XR	LEX-PO 200XR-FI	200	50	300	Roller bearing	235	140 x 110	105 x 75-80	11	54



Variants / Accessories

	With "Ideal-stop" brake *
Technical description page	77
Ref. No. extension	-IS
Available for wheel Ø [mm]	160 + 200

* Without alteration of the total height.