


Series: LEXR-PO

Stainless steel swivel castors with bolt hole fitting

 150 - 300 kg



Brackets: LEXR Series - Pressed from high-quality, chromium-nickel stainless steel (material No. 1.4301/AISI 304), with double ball bearing in the swivel head, with strong central kingpin, bolted wheel axle. All metal parts are stainless steel and brackets are vibration-ground finished.
Detailed description: Page 68 and 76.

Wheels: PO Series - Made of high-quality nylon, colour natural white, high abrasion resistance, low rolling resistance, smooth running performance on even floors, shock and impact-resistant, corrosion-resistant, high chemical resistance to alcohol, salts, greases and certain acids and lyes in diluted concentration, plain bearing.
Detailed description: Page 240, 241 and 47.

Swivel castors		Swivel castors with "stop-fix" brake							
Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset [mm]
LEXR-PO 75G	LEXR-PO 75G-FI	75	32	150	Plain bearing	100	70	13	38
LEXR-PO 80G	LEXR-PO 80G-FI	80	33	150	Plain bearing	102	70	13	38
LEXR-PO 100G	LEXR-PO 100G-FI	100	37	150	Plain bearing	125	70	13	36
LEXR-PO 125G	LEXR-PO 125G-FI	125	40	150	Plain bearing	150	70	13	40
LEXR-PO 150G	LEXR-PO 150G-FI	150	50	300	Plain bearing	190	88	13	54
LEXR-PO 200G	LEXR-PO 200G-FI	200	50	300	Plain bearing	235	88	13	54

