

Series: LEXZ-PO

**Stainless steel swivel castors with stem fitting**

 150 - 270 kg



**Brackets:** LEXZ Series - Pressed from high-quality, chromium-nickel stainless steel (material No. 1.4301/AISI 304), swivel bracket with double ball bearing in the swivel head, plug-in stem, bolted wheel axle. All metal parts are stainless steel and brackets are vibration-ground finished.  
Detailed description: Page 68 and 76.

**Wheels:** PO Series - Made of high-quality nylon, colour natural white, high abrasion resistance, low rolling resistance, smooth running performance on even floors, shock and impact-resistant, corrosion-resistant, high chemical resistance to alcohol, salts, greases and certain acids and lyes in diluted concentration, plain bearing.  
Detailed description: Page 240, 241 and 47.

Swivel castors		Swivel castors with "stop-fix" brake		Wheel Ø	Wheel width	Load capacity	Bearing version	Total height	Stem Ø	Stem length	Offset
Ref. No.	Ref. No.	[mm]	[mm]	[kg]	[mm]	[mm]		[mm]	[mm]	[mm]	[mm]
LEXZ-PO 75G	LEXZ-PO 75G-FI	75	32	150	Plain bearing	100	20	50	38		
LEXZ-PO 80G	LEXZ-PO 80G-FI	80	33	150	Plain bearing	102	20	50	38		
LEXZ-PO 100G	LEXZ-PO 100G-FI	100	37	150	Plain bearing	125	20	50	36		
LEXZ-PO 125G	LEXZ-PO 125G-FI	125	40	150	Plain bearing	150	20	50	40		
LEXZ-PO 150G	LEXZ-PO 150G-FI	150	50	270	Plain bearing	190	27	60	54		
LEXZ-PO 200G	LEXZ-PO 200G-FI	200	50	270	Plain bearing	235	27	60	54		

