

Series: LX-PO, BX-PO

Stainless steel swivel and fixed castors, medium duty brackets

400 kg



Brackets: LX/BX Series - Pressed from high-quality, chromium-nickel stainless steel (material No. 1.4301/AISI 304), swivel bracket with double ball bearing in the reinforced swivel head, swivel head sealing, strong central kingpin, bolted wheel axle. All metal parts are stainless steel and brackets are vibration-ground finished. Top plate drawings: Page 71. Detailed description: Page 68 and 76.

Wheels: PO Series - Made of high-quality nylon, colour natural white, high abrasion resistance, low rolling resistance, smooth running performance on even floors, shock and impact-resistant, corrosion-resistant, high chemical resistance to alcohol, salts, greases and certain acids and lyes in diluted concentration, plain, stainless steel roller or ball bearing. Detailed description: Page 241 and 47.

Swivel castors

Fixed castors

Swivel castors with "stop-fix" brake

Ref. No.	Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LX-PO 150G	BX-PO 150G	LX-PO 150G-FI	150	50	400	Plain bearing	190	140 x 110	105 x 75-80	11	60
LX-PO 150XR	BX-PO 150XR	LX-PO 150XR-FI	150	50	400	Roller bearing	190	140 x 110	105 x 75-80	11	60
LX-PO 150XK	BX-PO 150XK	LX-PO 150XK-FI	150	50	400	Ball bearing	190	140 x 110	105 x 75-80	11	60
LX-PO 200G	BX-PO 200G	LX-PO 200G-FI	200	50	400	Plain bearing	235	140 x 110	105 x 75-80	11	65
LX-PO 200XR	BX-PO 200XR	LX-PO 200XR-FI	200	50	400	Roller bearing	235	140 x 110	105 x 75-80	11	65
LX-PO 200XK	BX-PO 200XK	LX-PO 200XK-FI	200	50	400	Ball bearing	235	140 x 110	105 x 75-80	11	65

