

Series: LI-VEHI, BE-VEHI, B-VEHI

**Heat-resistant pressed steel
swivel and fixed castors**

 65 - 180 kg

 -30°C to +200°C



Brackets: LI/BE/B Series - Pressed steel, swivel bracket with double ball bearing in the swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely long service life, heat-resistant grease and adjusted bearing play, bolted wheel axle, zinc-plated.
Top plate drawings: Page 71.
Detailed description: Page 69.

Wheels: VEHI Series - Tyres: Heat-resistant solid rubber Blickle® Hot, colour black, 80° shore A.
Rims: Pressed steel, roller bearing, zinc-plated.
Detailed description: Page 330 and 52.

Temperature range from -30°C to +200°C.

Swivel castors

Fixed castors

| Ref. No. | Ref. No. | Wheel Ø [mm] | Tyre width [mm] | Load capacity [kg] | Bearing version | Total height [mm] | Plate size [mm] | Bolt hole spacing [mm] | Bolt hole Ø [mm] | Offset swvl castor [mm] |
|--------------|--------------|-----------------|-----------------------|--------------------------|--------------------|-------------------------|-----------------------|------------------------------|------------------------|----------------------------------|
| LI-VEHI 100R | BE-VEHI 100R | 100 | 30 | 65 | Roller bearing | 125 | 100 x 85 | 80 x 60 | 9 | 36 |
| LI-VEHI 125R | BE-VEHI 125R | 125 | 37,5 | 90 | Roller bearing | 150 | 100 x 85 | 80 x 60 | 9 | 40 |
| LI-VEHI 160R | B-VEHI 160R | 160 | 40 | 120 | Roller bearing | 195 | 140 x 110 | 105 x 75-80 | 11 | 60 |
| LI-VEHI 200R | B-VEHI 200R | 200 | 50 | 180 | Roller bearing | 235 | 140 x 110 | 105 x 75-80 | 11 | 65 |

