

Series: LIXR-VKHT

Heat-resistant stainless steel swivel castor with bolt hole fitting

 100 kg

 -30°C to +280°C




Swivel castor

Brackets: LIXR Series - Pressed from high-quality, chromium-nickel stainless steel (material No. 1.4301/AISI 304), single bolt hole fitting, double ball bearing in the swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely long service life, strong central kingpin, Teflon-coated stainless steel axle tube and bolted wheel axle. All metal parts are stainless steel and brackets are vibration-ground finished. **Particularly suitable for oven racks, swivel head without grease, extremely smooth rolling characteristics.**
Detailed description: Page 69.

Wheels: VKHT Series - Tyres: Heat-resistant Blickle® Hotline-Special solid rubber, colour black, 80° shore A. Rims: Made of special, heat-resistant synthetic, plain bearing, colour black.
Detailed description: Page 333 and 52.

Temperature range from -30°C to +260°C (temporarily up to +280°C).

Ref. No.	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset [mm]
LIXR-VKHT 100G-OF	100	30	100	Plain bearing	125	70	13	36



Variants / Accessories

With heat-resistant grease
-30° C to +260° C

Technical description page

Ref. No. LIXR-VKHT 100G

Available for wheel Ø [mm] Upon request