

Series: LI-G, BE-G, B-G

**Heat-resistant pressed steel  
swivel and fixed castors**

 150 - 400 kg

 -30°C to +300°C



**Brackets:** LI/BE/B Series - Pressed steel, swivel bracket with double ball bearing in the swivel head, dynamically pressed in accordance with special Blickle procedure resulting in an extremely long service life, heat-resistant grease and adjusted bearing play, bolted wheel axle, zinc-plated.  
Top plate drawings: Page 71.  
Detailed description: Page 69.

**Wheels:** G Series - Made of grey cast iron, very rugged, machined tread and tread edges, high abrasion resistance, low rolling resistance, insensitive to metal swarf, grease nipple, plain bearing, regular lubrication with high temperature grease required.  
Lacquered - colour silver.  
Detailed description: Page 343 and 49.

**Temperature range from -30°C to +270°C (temporarily up to +300°C).**

Swivel castors		Fixed castors								
Ref. No.	Ref. No.	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LI-G 80G	B-G 80G	80	25	150	Plain bearing	102	100 x 85	80 x 60	9	38
LI-G 100G	BE-G 100G	100	35	150	Plain bearing	125	100 x 85	80 x 60	9	36
LI-G 125G	BE-G 125G	125	35	150	Plain bearing	150	100 x 85	80 x 60	9	40
LI-G 150G	B-G 150G	150	50	400	Plain bearing	190	140 x 110	105 x 75-80	11	60
LI-G 200G	B-G 200G	200	50	400	Plain bearing	235	140 x 110	105 x 75-80	11	65