

Series: FSTH

**Guide rollers
with Blickle Extrathane[®] polyurethane tread,
steel wheel centre**

 45 - 245 kg



Treads: Made of Blickle Extrathane[®] polyurethane, firmly bonded, colour light brown, non-marking, 92° shore A, elastic, abrasion-resistant, high cut and tear propagation resistance, non-staining, floor-saving, low-noise operation, low rolling resistance, very good chemical connection with the wheel centre.

Wheel centres: Made of steel, ball bearing.
Detailed description: Page 56.

Guide rollers

Ref. No.	Wheel Ø (D) [mm]	Wheel width (T2) [mm]	Load capacity [kg]	Ball bearing	Axle bore Ø (d) [mm]	Clamping length (T1) [mm]
FSTH 40x13/10-8K	40	13	45	6000 ZZ	10	8
FSTH 40x15/10-8K	40	15	50	6000 2RS	10	8
FSTH 40x20/10-8K	40	20	70	6000 ZZ	10	8
FSTH 50x15/10-8K	50	15	65	6000 ZZ	10	8
FSTH 50x18/17-10K	50	18	80	6003 2RS	17	10
FSTH 60x20/15-13K	60	20	105	6302 ZZ	15	13
FSTH 60x20/20-12K	60	20	105	6004 2RS	20	12
FSTH 68x20/15-13K	68	20	115	6302 ZZ	15	13
FSTH 70x25/25-15K	70	25	155	6205 ZZ	25	15
FSTH 80x25/25-15K	80	25	170	6205 ZZ	25	15
FSTH 90x25/25-15K	90	25	185	6205 ZZ	25	15
FSTH 100x25/25-15K	100	25	215	6205 ZZ	25	15
FSTH 110x25/25-15K	110	25	230	6205 ZZ	25	15
FSTH 120x25/25-15K	120	25	240	6205 ZZ	25	15
FSTH 125x25/25-15K	125	25	245	6205 ZZ	25	15

Variants / Accessories



Further dimensions

Technical description page

Ref. No. extension

Upon request

